MATERIAL SAFETY DATA SHEET PRINTING INKS AND RELATED MATERIALS

#070

HMIS HAZARD RATING
HEALTH......1
FLAMMABILITY......1
PHYSICAL HAZARD.....0

Date prepared 05/15/2009 Prepared by Doug Chesley

Section I

PRODUCT CLASS: Gelled Petroleum Distillate
CHEMICAL & COMMON NAME: Komoplasm Reducer

MANUFACTURERS NAME & ADDRESS: Graphic Ink Co. 3135 W. DIRECTORS ROW S.L.C., UT.

EMERGENCY PHONE NUMBER: (801) 972-6142

Section II - HAZARDOUS INGREDIENTS

Ingredient: / Hazard Data:

NOT A HAZARDOUS MATERIAL / OSHA PEL: 5mg/m 3 (oil mist)

Section III - PHYSICAL DATA

Boiling Range: 570-680 F Percent volatile Wt.: 40-45%
Vapor Density vs. Air: LIGHTER Liquid Density vs. Water: LIGHTER
Appearance: PALE GREEN GELLED LIQUID Type of Odor: PETROLEUM DISTILLATE

Evaporation Rate vs. Butyl Acetone: SLOWER

Solubility in Water: INSOLUBLE

Section IV - FIRE & EXPLOSION DATA

Flammability Classification: COMBUSTIBLE OSHA: 1118 DOT: NOT REGULATED

Flashpoint: 310 F (test method-ASTM D-93) LEL- 1.1%

Extinguishing Media:

FOAM-(X) ALCOHOL FOAM-() CO2-(X) DRY CHEMICAL-(X) WATER FOG-()

Unusual Fire & Explosion Hazards: MAY GENERATE DENSE SMOKE WHEN BURNING.

MAY FOAM OR BOIL IN CONTACT WITH HOT WATER.

Special Firefighting procedures: USE POSITIVE PRESSURE SELF CONTAINED BREATHING

APPARATUS TO AVOID POTENTIALLY HARMFUL OR IRRITATING FUMES. (SCBA) EG. SCOTT AIR PACK

Section V - HEALTH HAZARD DATA

Effects of Over Exposure: EYE CONTACT WILL CAUSE IRRITATION. PROLONGED SKIN CONTACT MAY CAUSE IRRITATION. INHALATION MAY CAUSE RESPIRATORY DISCOMFORT

OSHA PEL: 5MG/3 (oil mist)

Medical conditions aggravated by exposure: NONE KNOWN.

Primary Route (s) or Entry: DERMAL - (X) INHALATION-(X)

Emergency & First Aid Procedures:

EYE CONTACT--FLUSH EYES FOR 15 MINUTES WITH WATER. SEEK MEDICAL ATTENTION, SKIN CONTACT--WASH EFFECTED AREAS WITH SOAP & WATER. REMOVE CONTAMINATED

CLOTHING & LAUNDER BEFORE WEARING. INHALATION--REMOVE TO FRESH AIR.

INGESTION--DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

KOMOPLASM PAGE 2

Section VI - REACTIVITY DATA

Product Stability: STABLE

Conditions To Avoid: EXTREME HEAT. PROLONGED OR REPEATED SKIN CONTACT.

SKIN CONTACT WHEN OVER 80 F. OXIDIZING AGENTS.

Section VII - SPILL OR LEAK PROCEDURES

Procedure if Material is Spilled or Released: LIMIT SPILL WITH SAND OR ABSORBENT MATERIAL. SHOVEL INTO CONTAINERS FOR RECOVERY OR DISPOSAL. WASH AREA WITH DETERGENT AND WATER.

Waste Disposal Method: LAND FILL APPROVED FOR INDUSTRIAL WASTES. INCINERATE

ONLY WHERE LOCAL REGULATIONS PERMIT. FOLLOW LOCAL GUIDELINES.

Section VIII - SPECIAL PROTECTION INFORMATION

Ventilation: GENERAL PLANT VENTILATION

Protection Gloves: SYNTHETIC RUBBER GLOVES MAY BE WORN SUBJECT TO EXPOSURE.

Respiratory Protection: NIOSH APPROVED AIR PURIFYING RESPIRATOR.

Eve Protection: GOGGLES OR FACE SHIELD MAY BE WORN.

Other Protective Equipment: PROTECTIVE OUTERWEAR IS RECOMMENDED.

Section IX - SPECIAL PRECAUTIONS

Handling & Storage: STORE UPRIGHT, IN SEALED METAL CONTAINERS AWAY FROM HEAT OR OPEN FLAMES. CLEAN UP SPILLS PROMPTLY, TO AVOID SLIPPING OR TRACKING.

Other Precautions: DO NOT TRANSFER INTO UNMARKED CONTAINERS.

The information and recommendations contained herein are proprietary, and are furnished solely for use by our customers. While believed to be true and accurate, they are offered solely for consideration, investigation and verification. NO GUARANTEE or WARRANTY of any kind is expressed or implied by Graphic Ink Co. with respect to this data. The applicability of Local, State, and Federal laws and regulations to this information must be determined by user.