MATERIAL SAFETY DATA SHEET PRINTING INKS AND RELATED MATERIALS

#000

HMIS HAZARD RATING HEALTH.....1 FLAMMABILITY.....1 R PHYSICAL HAZARD.....0

Date prepared 05/13/2009 Prepared by Doug Chesley

Section I

PRODUCT (CLASS: <u>ROLLER LUBE</u> CHEMICAL & COMMON NAME: <u>DEAD UNIT COMPOUND (AMBER)</u> MANUFACTURERS NAME & ADDRESS: Graphic Ink Co. 3135 W. DIRECTORS ROW S.L.C.,UT. EMERGENCY PHONE NUMBER: (801) 972-6142

Section II - HAZARDOUS INGREDIENTS	
Ingredient: /	Hazard Data:
/	
/	
NON HAZARDOUS INGREDIANTS	OSHA PEL: 5mg/m 3 (oil mist)
BY CURRENT OSHA STANDARDS	
PETROLATUM 100% /	
8009-03-8 /	
/	
Section III - PHYSICAL DATA	
Boiling Range: N/A	Percent volatile Wt.: 0% (EPA METHOD 24)
Vapor Density vs. Air: HEAVIER	Liquid Density vs. Water: HEAVIER
Appearance: AMBER PASTE	Type of Odor: NEGLIGIBLE
Evaporation Rate vs. Butyl Acetone: SLOWER	
Solubility in Water: INSOLUBLE	
Continue IV STOR & EVELOCION DATA	
Section IV - FIRE & EXPLOSION DATA	
Flammability Classification: COMBUSTIBLE	OSHA: 1118 DOT: NOT REGULATED
Flashpoint: 256 F (test method-ASTM D-93)	LEL- 1.1
Extinguishing Media:	
FOAM-(X) ALCOHOL FOAM-() CO2-(2)	X) DRY CHEMICAL-(X) WATER FOG-()
	x) DRT CHEMICAL-(X) WATERTOG-()
Unusual Fire & Explosion Hazards: MAY GENERATE DENSE SMOKE WHEN BURNING.	
•	
Special Firefighting procedures: USE SELF CONTAINED BREATHING APPARATUS	
TO AVOID POTENTIALLY HARMFUL OR IRRITATING FUMES.	
Section V - HEALTH HAZARD DATA	
Effects of Over Exposure: GENERALLY REGARDED AS NON TOXIC.	
EYE AND SKIN IRRITATION ARE POSSIBLE.	
Primary Route (s) or Entry: DERMAL - (X)	INHALATION-()
Emergency & First Aid Procedures:	
EYE CONTACTFLUSH EYES FOR 15 MINUTES WITH WATER. SEEK MEDICAL ATTENTION,	
SKIN CONTACTWASH EFFECTED AREAS WITH SOAP & WATER. REMOVE CONTAMINATED	
CLOTHING & LAUNDER BEFORE WEARING.	

INHALATION--REMOVE TO FRESH AIR.

INGESTION--DO NOT INDUCE VOMITING. SEEK MEDICAL ATTENTION.

Roller Putz

Section VI - REACTIVITY DATA

PAGE 2

Product Stability: STABLE

Conditions To Avoid: EXTREME HEAT. STRONG OXIDIZING AGENTS

Section VII - SPILL OR LEAK PROCEDURES

Procedure if Material is Spilled or Released: SCRAPE UP BULK WITH INK OR PUTTY KNIFE, WASH AREA WITH DETERGENT AND WATER, PROVIDE ADEQUATE VENTILATION DURING CLEAN UP.

Waste Disposal Method: LAND FILL APPROVED FOR INDUSTRIAL WASTES. INCINERATE ONLY WHERE LOCAL REGULATIONS PERMIT.

Section VIII - SPECIAL PROTECTION INFORMATION

Ventilation: GENERAL PLANT VENTILATION, IN ACCORDANCE WITH GOOD ENGINEERING PRACTICE TO KEEP OIL MIST CONCETATIONS BELOW THE PEL.

Protection Gloves: SYNTHETIC RUBBER GLOVES SHOULD BE WORN SUBJECT TO EXPOSURE. Respiratory Protection: NOT REQUIRED

Eye Protection: GOGGLES OR FACE SHIELD MAY BE WORN.

Other Protective Equipment: PROTECTIVE OUTERWEAR IS RECOMMENDED. WASH HANDS BEFORE EATING OR SMOKING.

Section IX - SPECIAL PRECAUTIONS

Handling & Storage: STORE UPRIGHT, IN SEALED METAL CONTAINERS AWAY FROM HEAT OR OPEN FLAMES. CLEAN UP SPILLS PROMPTLY, TO AVOID SLIPPING OR TRACKING. Other Precautions: DO NOT TRANSFER INTO UNMARKED CONTAINERS.

The information and recommendations contained herein are proprietary, and are furnished solely for use by our customers. While believed to be true and accurate, they are offered solely for consideration, investigation and verification. NO GUARANTEE or WARRANTY of any kind is expressed or implied by Graphic Ink Co. with respect to this data. The applicability of Local, State, and Federal laws and regulations to this information must be determined by user.